Shakespeare

Installing the Cell Phone Adapter

The Style CPA-110 Cell Phone Adapter lets you connect Motorola MicroTAC[™], MicroTAC[™] II, PL 550/950, or Slim Lite phones to your boat's cellular antenna.

Installation Instructions

- 1. Extend the cell phone's retractable antenna as far as it will go.
- 2. Unsnap the antenna's black base cap at its base with a thin bladed screwdriver. See picture #1.
- 3. Pull the coil assembly out of its socket and slide it away from the phone along the antenna.



- 4. Unscrew the antenna from the phone by twisting it counterclockwise. See picture #2.
- 5. Snap the (supplied) black replacement flexible antenna into place in the phone's antenna socket. The small metal connector at its base should point toward the back of the cell phone. See picture #3.



- 6. Snap the supplied replacement black cap into position. See picture #4.
- 7. Connect the adapter cable to your ship's antenna, and plug the other end into the connection at the base of the replacement antenna.







Supplied Parts

- 1 Antenna adapter cable
- 1 Replacement black cap
- 1 Replacement flex antenna

Shakespeare Electronic Products Group · Marine Products

6111 Shakespeare Rd., Columbia, SC 29223 · 803-227-1590 · Fax: 803-419-3099 www.shakespeare-marine.com